



NTN BEARING DRIVESHAFT,INC.



2.756 Inch | 70 Millimeter x 5.906 Inch | 150
Millimeter x 1.378 Inch | 35 Millimeter SKF NU
314 ECM/C3 Cylindrical Roller Bearings

Bearing No. NU 314 ECM/C3

NU 314 ECM/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	1.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.23
EAN	7316576623677
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	70MM Bore; Straight Bore Profile; 150MM Outside Diameter; 35MM Width;



NTN BEARING DRIVESHAFT,INC.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inter
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 314 ECM/C3
Weight / LBS	7.108
D	5.906 Inch 150 Millimeter
B	1.378 Inch 35 Millimeter
d	2.756 Inch 70 Millimeter
bore diameter:	70 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	150 mm
maximum rpm:	5600 RPM
overall width:	35 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	35 mm



NTN BEARING DRIVESHAFT,INC.

operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	236 kN
series:	NU3
static load capacity:	228 kN